



Safety Data Sheet

Version: 2.1.1.2

Issue Date:

Page 1 of 2

---

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

---

#### PRODUCT NAMES

N18 CEILING BATTEN  
N23, N08 & N29 FURRING CHANNEL  
N27 & N28 TOP CROSS RAIL  
AB ANGLE BRACE  
BA BACKING ANGLE  
N40, N41 & N42 WALL TRACK  
STEEL STUD, TRACK AND DEFLECTION HEAD

#### PRODUCT USE

Used in construction of drywall framing and timber frame bracing.

#### SUPPLIER

Company: Nashco Address:  
28 Carrington Street  
Queanbeyan  
NSW, 2620  
Australia  
Telephone: +61 2 6124 3400  
Fax: +61 2 6297 9740

---

### Section 2 - HAZARDS IDENTIFICATION

---

#### STATEMENT OF HAZARDOUS NATURE

Not Applicable

#### RISK

Risk Codes	Risk Phrase
------------	-------------

None Applicable

#### SAFETY

Safety Codes	Safety Phrases
--------------	----------------

S36	Wear suitable protective clothing
-----	-----------------------------------

S37	Wear suitable gloves
-----	----------------------

---

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

All products manufactured by Nashco are produced from high quality Zinc coated steel coil material which is classified as a non- hazardous material. Kerosene is applied to the product during the manufacturing process however this evaporates quickly.

---

### Section 4 - FIRST AID MEASURES

---

#### SKIN

Damage to skin through cuts should be treated through regular bandaging techniques. If there is any reaction with the skin to the product, consider using different gloves when handling and or using barrier cream or cease handling the product.

---

**Section 5 - FIRE FIGHTING MEASURES**

---

Not Applicable

---

**Section 6 - ACCIDENTAL RELEASE MEASURES**

---

Not Applicable

---

**Section 7 - HANDLING AND STORAGE**

---

**PROCEDURE FOR HANDLING**

- Use protective clothing including gloves.
- Practice approved manual handling techniques as outlined in AS – 1470 Health and safety at work.

**STORAGE REQUIREMENTS**

- Store out of the weather when storing for prolonged periods.
- Store away from airborne contaminants such as acid and salt spray.